

PH3-LLT MK2 Proving Unit

Essential Proving Unit for use with the LLT MK2 Voltage Indicator



Designed for use with the Live Line Tester (LLT) MK2, the PH3 MK2 is a highly portable, battery powered unit for proving the live line testers function in the field.

This proving unit produces a DC output voltage from a 9v PP3 battery source that lights up the red indicator when active.

It is essential to prove that the Live Line Tester is functional both before and after testing the DC system to be worked on.

The MK2 version has an integrated case that protects the unit when not in use. The wider base improves stability when using the unit in the field and also holds the operating instructions for added convenience and ease of use.

Key Features:

- > Red indication showing when the unit is active
- > Integrated case to protect the unit
- > Wide base to aid stability on uneven ground
- > Instructions for use printed on the case

Together, we're making our world a safer place.
Every. Single. Day.

T: +44 (0) 191 587 8741 E: sales@seaward.com



SEAWARD
TESTED. TRUSTED... WORLDWIDE.

Enquire about the NEW **PH3 LLT MK2 Proving Unit** at
seaward.com/PH3-MK2



Optional Accessories:

- > Live Line Tester (LLT) MK2 (423A910)
- > Kit carry case (308A955)

Technical Specification:

Electrical Specificaion

Output Voltage	500V dc nominal
Output Current	10mA into 2kohm

General Specification:

Physical Dimensions

External Dimensions	175 x 115 x 47 mm
Weight	0.16kg
Range Temperature	-10 / 80°C

Rev 2

Together, we're making our world a safer place.
Every. Single. Day.

T: +44 (0) 191 587 8741 E: sales@seaward.com



SEAWARD

TESTED. TRUSTED... WORLDWIDE.

Enquire about the NEW **PH3 LLT MK2 Proving Unit** at
seaward.com/PH3-MK2