


SDR Series

HV Safe Discharge Rod

Rods for the safe damp discharge of cables or equipment under test up to 35kv

The SDR11 and 35 are safe discharge rods, designed to conduct the safe damp discharge of residual charge on a cable or piece of electrical equipment with volages up to 11kV and 35kV respectively by limiting the discharge current.

The SDR series features high grade glass fibre tubing and incorporates encapsulated resistor chains and are supplied with flexible cable with a heavy duty brass clamp for easy earth connection.



Key Features

- Safe HV discharge rod for safe damp discharge of cables and / or equipment under test
- Supplied with flexible cable with heavy duty brass clamp for easy earth connection
- Robust single pole device
- No switches
- Suitable for voltages to 11kV/35kV
- Supplied with cushion soft carrying case

Standard Accessories (supplied with SDR11 and SDR35)

- Earthing wire 10 sq.mm x 5mtr
- Yellow green wire
- Carry case

Technical Specification

	SDR11	SDR35
Discharge Voltage:	11kV AC/DC Maximum	35kV AC/DC Maximum
Peak Discharge Current:	1.1A for 100ms	3.5A for 100ms
Bleeder Resistance:	10K ohm	10K ohm
Discharge Capacitance:	10 μ F	6 μ F
Leakage Current at 35 KV AC:	<50 μ A	< 50 μ A
Discharge Energy:	3675J	3675J
Cooling:	Neutral	Neutral
Total Size:	32mm x 750mm	32mm x 950mm
Weight:	2.2 kg (Net)	2.2 kg (Net)
Temperature:	-5°C to 70°C	-5°C to 70°C
Safety:	IEC 61230, EMC Not Applicable	IEC 61230, EMC Not Applicable

Part numbers:
SDR11: 401A912
SDR35: 401A910

Rev 1.2